

PF6404 MPA



DIMENSIONI DIMENSIONS	910x880x635 mm WxDxH
CAPACITA' TEGLIE NUMBER OF TRAYS	4 TG 600x400
PASSO - PITCH	80 mm
ALIMENTAZIONE FEEDING TYPE	400V~ 3N 50Hz
POTENZA - POWER	7,6 kW
TEMPERATURA MAX MAX TEMPERATURE	270 °C
PESO - WEIGHT	64 kg
UMIDIFICAZIONE HUMIDIFICATION	SI YES

CARATTERISTICHE TECNICHE

- Camera di cottura in AISI 304 acciaio inox 18/10
- Camera di cottura con spigoli arrotondati per facilitarne la pulizia
- Lampada alogena interna
- Pannello di controllo analogico (meccanico)
- Produzione di vapore con iniezione diretta dell'acqua
- Controllo analogico percentuale vapore (da "0" a "100%")
- Gruppi motori/ventole bidirezionali per una cottura omogenea
- Resistenze corazzate
- Vetro esterno porta "Freddo"
- Porta con vetri temperati
- Guarnizione porta in materiale resistente alle alte temperature
- Tubo di scarico per acqua e residui della cottura

TECHNICAL FEATURES

- Cooking chamber made of AISI 304 18/10 stainless steel
- Rounded chamber for better cleaning
- Halogen Internal light
- Analogic control panel
- Steam production with water direct injection
- Analogic humidity control (from "0" to "100%")
- Bidirectional fans for even cooking
- Sheathed heating elements
- Cold external glass
- Door with tempered glasses
- Door gasket with high temperature resistance
- Baking/cooking water discharge plug

PRODOTTI ABBINABILI / OPTIONALS:



Lievitatore - Proofer
PL6410U



Lievitatore - Proofer
PL6404U - PL6404



Cappa - Hood
PC6404



Supporto - Stand
PS6404S - PS6410S

