

## PF6404 MGA



|                                     |                         |
|-------------------------------------|-------------------------|
| DIMENSIONI<br>DIMENSIONS            | 910x880x635 mm<br>WxDxH |
| CAPACITA' TEGLIE<br>NUMBER OF TRAYS | 5 - GN1/1               |
| PASSO - PITCH                       | 67 mm                   |
| ALIMENTAZIONE<br>FEEDING TYPE       | 400V~ 3N 50Hz           |
| POTENZA - POWER                     | 7,6 kW                  |
| TEMPERATURA MAX<br>MAX TEMPERATURE  | 270 °C                  |
| PESO - WEIGHT                       | 64 kg                   |
| UMIDIFICAZIONE<br>HUMIDIFICATION    | SI<br>YES               |

### CARATTERISTICHE TECNICHE

- Camera di cottura in AISI 304 acciaio inox 18/10
- Camera di cottura con spigoli arrotondati per facilitarne la pulizia
- Lampada alogena interna
- Pannello di controllo analogico (meccanico)
- Produzione di vapore con iniezione diretta dell'acqua
- Controllo analogico percentuale vapore (da "0" a "100%")
- Gruppi motori/ventole bidirezionali per una cottura omogenea
- Resistenze corazzate
- Vetro esterno porta "Freddo"
- Porta con vetri temperati
- Guarnizione porta in materiale resistente alle alte temperature
- Tubo di scarico per acqua e residui della cottura

### TECHNICAL FEATURES

- Cooking chamber made of AISI 304 18/10 stainless steel
- Rounded chamber for better cleaning
- Halogen Internal light
- Analogic control panel
- Steam production with water direct injection
- Analogic humidity control (from "0" to "100%")
- Bidirectional fans for even cooking
- Sheathed heating elements
- Cold external glass
- Door with tempered glasses
- Door gasket with high temperature resistance
- Baking/cooking water discharge plug

### PRODOTTI ABBINABILI / OPTIONALS:



Lievitatore - Proofer  
PL6404 - PL6404U



Lievitatore - Proofer  
PL6410U



Cappa - Hood  
PC6404



Supporto - Stand  
PS6404S - PS6410S

