

PL6404 MU



DIMENSIONI DIMENSIONS	920x745x890mm WxDxH
CAPACITA' TEGLIE NUMBER OF TRAYS	8 TG 600x400
PASSO - PITCH	70 mm
ALIMENTAZIONE FEEDING TYPE	230V~ 1N 50/60Hz
POTENZA - POWER	1,1 kW
TEMPERATURA MAX MAX TEMPERATURE	70 °C
PESO - WEIGHT	43kg
UMIDIFICAZIONE HUMIDIFICATION	SI YES

CARATTERISTICHE TECNICHE

TECHNICAL FEATURES

- Struttura in acciaio inox AISI 430
- Pannello di controllo analogico (meccanico)
- Umidificazione con iniezione dell'acqua su vaschetta riscaldata
- Pulsante per attivazione umidificazione
- Resistenze corazzate
- Piedini in acciaio inox regolabili
- Porta con vetri temperati
- Guarnizione porta in materiale resistente alle alte temperature
- Vaschetta esterna removibile per raccolta condensa

- Body and internal components made of AISI 430 stainless steel
- Analogic control panel
- Humidification with water injection on internal heated tray
- Push botton switch to activate humidification
- Sheathed heating elements
- Leveling feet made in stainless steel
- Door with tempered glasses
- Door gasket with high temperature resistance
- Removable external drip box

ACCESSORI / OPTIONALS:



Ruote - Wheels



Stratog S.r.l. a Socio unico
Via Cecon 15C, - 35010 Loreggia (PD) ITALY
Tel. +39 049/9336426 - Fax. +39 049/9336426
info@stratog.it - P. IVA 04605740283

www.stratog.it



100% Made in Italy

